



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### 1. Identification

**Product identifier** ProFin<sup>®</sup>Satin

**Other means of identification**

**SDS number** 10

**Synonyms** 15570

**Recommended use** Not available.

**Recommended restrictions** Not available.

#### Manufacturer/Importer/Supplier/Distributor information

**Manufacturer/Supplier** Daly's Wood Finishing Products,  
4522 S 133<sup>rd</sup> St,  
Tukwila, WA 98168.

**General Assistance** (206) 244-8844, toll free: (800) 727-9694

**E-Mail** info@dalyswoodfinishes.com

**Contact Person** Not available.

**Emergency Telephone** Chemtrec : 800-424-9300

### 2. Hazard(s) Identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure; Narcotic effects	Category 3
	Aspiration hazard	Category 1

#### Label elements



**Signal word** Danger

**Unknown Toxicity** 53 % of the mixture consists of ingredient(s) of unknown toxicity.

**Hazard statement** Flammable liquid and vapour. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### Precautionary statement

#### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take action to prevent static discharges. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

#### Response

IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use CO<sub>2</sub>, dry chemical, foam, water spray for extinction. IF SKIN irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and Keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Storage

Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Hazard(s) not otherwise classified (HNOC)

None known.

### 3. Composition/information on ingredients

#### Mixtures

<u>Chemical name</u>	<u>CAS number</u>	<u>%</u>
Mineral spirits	64742-47-8	40
Xylenes	1330-20-7	6
Ethylbenzene	100-41-4	
Amorphous Silica	761-86-9	2
Ethene	9002-88-4	
N-Methyl-2-pyrrolidone	872-50-4	<1



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### 4. First-aid measures

<b>Inhalation</b>	Move individual to fresh air. If breathing has stopped, apply artificial respiration, get medical attention immediately.
<b>Skin contact</b>	Wash area with soap and water. If irritation persists, get medical attention.
<b>Eye contact</b>	Wash with clean water for at least fifteen minutes; get medical attention.
<b>Ingestion</b>	DO NOT INDUCE VOMITING. Give water or milk to drink; Get medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	May cause redness, irritation of eye. Inhalation may cause dizziness, headache, nausea, possible nervous system depression. Ingestion may cause nausea, gastrointestinal irritation, or vomiting. When comes in contact with skin may cause rash, cracking, dryness or defatting of skin. Pre-existing lung or skin conditions could be aggravated by repeated exposure.
<b>Indication of immediate medical attention and special treatment needed</b>	Keep victim warm and rested. Avoid any direct contact with the product. Never give anything by mouth to an unconscious person. Pre-existing lung or skin conditions could be aggravated by repeated exposure. Treat symptomatically.
<b>General information</b>	If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	CO <sub>2</sub> , dry chemical, foam, water spray.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	None known.
<b>Special protective equipment and Special firefighting procedures</b>	Fight as a volatile fire; do not enter enclosed or confined fire spaces without proper protective equipment. This may include self-contained breathing apparatus.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Use only non-sparking tools. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### Environmental Precautions

Avoid discharge into drains, water courses or onto the ground.

#### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Provide ventilation. Take precautionary measures against static discharge. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Rags and absorbent material should be immersed in water. For waste disposal, see section 13 of the SDS.

### 7. Handling and storage

#### Precautions for safe handling

Store away from high temperature, sparks, or open flame. Read and observe all precautions on product label.

#### Conditions for safe storage

KEEP OUT OF REACH OF CHILDREN. Store in original container; keep tightly closed. Do not reuse container for other purposes. Store away from incompatible materials.

#### Incompatible materials

Avoid strong oxidizing agents.

### 8. Exposure controls/personal protection

#### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Mineral spirits	PEL (TWA)	500 ppm
Xylene	PEL (TWA)	100 ppm (435 mg/m <sup>3</sup> )
Ethyl benzene	PEL (TWA)	100ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Mineral spirits	TWA	500 ppm
Ethyl benzene	TWA	100ppm



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

Xylene TWA 100 ppm (435 mg/m<sup>3</sup>)

### US. OSHA Table Z-2 (29 CFR 1910.1000)

None of the chemical in this product is listed.

### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Amorphous silica	TWA	20mppf

### US. ACGIH Threshold Limit Values

Components	Type	Value
Ethyl benzene	TLV(TWA)	200ppm
Xylene	TLV(TWA)	100 ppm
	TLV(ST)	150 ppm

### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Mineral spirits	REL (TWA)	350 mg/m <sup>3</sup>
	REL (Ceiling)	1800 mg/m <sup>3</sup> (15-minute)
Ethyl benzene	REL (TWA)	100ppm
	REL (ST)	125ppm
Xylene	REL (TWA)	100 ppm (435 mg/m <sup>3</sup> )
	REL(ST)	150 ppm (655 mg/m <sup>3</sup> )

### Appropriate engineering controls

Provide adequate ventilation. Provide local exhaust or general room ventilation to minimize vapour concentrations. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear goggles or face shield.

#### Skin protection

##### Hand protection

Use Neoprene or rubber gloves.

##### Other

Eyewash station should be available; impervious protective clothing.

#### Respiratory protection

Wear NIOSH-approved respirator for organic vapors. Ensure workers are trained in their proper use.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

out of the workplace. Eye wash fountain and emergency showers are recommended.

### 9. Physical and chemical properties

<b>Appearance</b>	Pale yellow liquid.
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Pale yellow.
<b>Odor</b>	Petroleum distillate odor.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	300-405 °F
<b>Flash point</b>	107 °F
<b>% Volatile by Volume</b>	70%
<b>Evaporation rate (BuOAc=1)</b>	0.13
<b>Maximum Volatile Organic Compound (V.O.C.)</b>	550 g/l
<b>Flammability (solid, liquid, gas)</b>	Flammable liquid and vapor.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit – lower (%)</b>	Not available.
<b>Flammability limit – upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	1.0
<b>Explosive limit - upper (%)</b>	6.0
<b>Vapor pressure (mm Hg)</b>	5mm Hg at 77 °F
<b>Vapor density (Air=1)</b>	4.9
<b>Relative density (Specific gravity)</b>	0.87
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble.
<b>Solubility (other)</b>	Soluble in petroleum solvents.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.

### 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

**Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**Conditions to avoid**

None known.

**Incompatible materials**

Avoid strong oxidizing agents.

**Hazardous decomposition Products**

Usual products of combustion CO, CO<sub>2</sub>, possibly acrolein, and oxides of nitrogen.

### 11. Toxicological information

#### Information on likely routes of exposure

**Ingestion**

May cause nausea, gastrointestinal irritation, or vomiting.

**Inhalation**

May cause dizziness, headache, nausea, possible nervous system depression.

**Skin contact**

May cause rash, cracking, dryness or defatting of skin.

**Eye contact**

May cause redness, irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

May cause redness, irritation of eye. Inhalation may cause dizziness, headache, nausea, possible nervous system depression. Ingestion may cause nausea, gastrointestinal irritation, or vomiting. When comes in contact with skin may cause May cause rash, cracking, dryness or defatting of skin.

**Delayed and immediate effects and also chronic effects from short- and long-term exposure**

Pre-existing lung or skin conditions could be aggravated by repeated exposure.

#### Numerical measures of toxicity

##### Components

Mineral spirits (CAS 64742-47-8)

##### Test

##### Species

##### Test Results

Oral LD<sub>50</sub>

Rat

>5000 mg/kg

Dermal LD<sub>50</sub>

Rabbit

>2000 mg/kg

Inhalation LC<sub>50</sub>

Rat

> 5.28 mg/l,4h

Ethyl benzene (CAS 100-41-4)

Oral LD<sub>50</sub>

Rat

3500 mg/kg

Dermal LD<sub>50</sub>

Rabbit

15400 mg/kg

Inhalation LC<sub>50</sub>

Rat

17.4 mg/l, 4h

Xylene (CAS 1330-20-7)

Oral LD<sub>50</sub>

Rat

3523 mg/kg

Dermal LD<sub>50</sub>

Rabbit

4300 mg/kg

Inhalation LC<sub>50</sub>

Rat

6350 ppm, 4h

N-Methyl-2-Pyrrolidone (CAS 872-50-4)

Oral LD<sub>50</sub>

Rat

3914 mg/kg

Dermal LD<sub>50</sub>

Rabbit

8000 mg/kg

Inhalation LC<sub>50</sub>

Rat

>501 mg/l,4h

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitization**

**Respiratory sensitization**

No data available.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

<b>Skin sensitization</b>	No data available.
<b>Germ cell mutagenicity</b>	No data available.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Ethyl benzene (CAS 100-41-4)	2B "Possibly carcinogenic to humans".
<b>NTP Report on Carcinogens</b>	
Ethyl benzene (CAS 100-41-4)	Not listed.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Ethyl benzene (CAS 100-41-4)	Not listed.
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

### 12. Ecological information

#### Numerical measures of toxicity

Components	Test	Species	Test Results
Mineral spirits (CAS 64742-47-8)	Fish LC <sub>50</sub>	Bluegill ( <i>Lepomis macrochirus</i> )	2.2 mg/l, 96h
Xylene (CAS 1330-20-7)	Fish LC <sub>50</sub>	Fathead minnow ( <i>Pimephales promelas</i> )	13.4 mg/l, 96h
	Crustacea EC <sub>50</sub>	Water flea ( <i>Ceriodaphnia dubia</i> )	> 3.4 mg/L, 48h
	Algae EC <sub>50</sub>	Microalga ( <i>Selenastrum capricornutum</i> )	4.9 mg/l, 72h
Ethyl benzene (CAS 100-41-4)	Fish LC <sub>50</sub>	Rainbow trout ( <i>Oncorhynchus mykiss</i> )	>500 mg/l,96h
	Crustacea EC <sub>50</sub>	Water flea ( <i>Daphnia magna</i> )	>1000 mg/l,48h
	Algae EC <sub>50</sub>	Green algae ( <i>Scenedesmus subspicatus</i> )	>500 mg/l,72h
N-Methyl-2-Pyrrolidone (CAS 872-50-4)		Rainbow trout ( <i>Oncorhynchus mykiss</i> )	>500 mg/l,96h
		Water flea ( <i>Daphnia magna</i> )	1.23 mg/l,48h
	Algae EC <sub>50</sub>	Green algae ( <i>Scenedesmus subspicatus</i> )	>500 mg/l,72h



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

**Persistence and degradability**  
**Bioaccumulative potential**  
**Mobility in soil**  
**Other adverse effects**

No information available.  
No information available.  
No information available.  
No information available.

### 13. Disposal considerations

**Disposal instructions**

Rags and absorbent material should be immersed in water. Dispose of in accordance with all federal, state and local regulations.

**Hazardous waste code**

**US RCRA Hazardous Waste U List : Reference**

Xylene (CAS 1330-20-7)

U239

**Waste from residues / unused products**

None known.

**Contaminated packaging**

The treatment and disposal should be evaluated specifically for each product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse container for other purposes.

### 14. Transport information

**DOT**

**UN number**

UN 1263

**UN proper shipping name**

PAINT RELATED MATERIAL

**Transport hazard class(es)**

**Class**

3

**Subsidiary risk**

-

**Label(s)**

3 - Flammable liquid



**Packing group**

III

**Environmental hazards**

**Marine pollutant**

Yes

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### IATA

**UN number** UN 1263  
**UN proper shipping name** Paint related material  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3 - Flammable liquid



**Packing group** III  
**Environmental hazards** Yes  
**ERG Code** 3L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

### IMDG

**UN number** UN 1263  
**UN proper shipping name** PAINT RELATED MATERIAL  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3-Flammable liquid



**Packing group** III  
**Environmental hazards**  
**Marine pollutant** Yes  
**EmS** F-E, S-D  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

### 15. Regulatory information

#### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Some components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None of the chemicals in this product is listed.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Mineral spirits (CAS 64742-47-8)

Xylene (CAS 1330-20-7)

Ethyl benzene (CAS 100-41-4)

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Xylene (CAS 1330-20-7)

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories			
Immediate Hazard	-	Yes	
Delayed Hazard	-	Yes	
Fire Hazard	-	Yes	
Pressure Hazard	-	No	
Reactivity Hazard	-	No	

#### SARA 302/304 Extremely hazardous substance

None of the chemical in this product is listed.

SARA 311/312 Hazardous chemical Yes

#### SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Xylene	1330-20-7	6
Ethylbenzene	100-41-4	

#### Other federal regulations

##### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

Ethylbenzene (CAS 100-41-4)

##### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None of the chemicals in this product is listed.

##### Safe Drinking Water Act (SDWA)

None of the chemicals in this product is listed.

#### US State regulations

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects.

##### US. New Jersey Worker and Community Right-to-Know Act

Xylene (CAS 1330-20-7)

Ethylbenzene(CAS 100-41-4)



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

N-Methyl-2-pyrrolidinone (CAS 872-50-4)

**US. Pennsylvania Worker and Community Right-to-Know Law**

N-Methyl-2-pyrrolidinone (CAS 872-50-4)

Ethylbenzene(CAS 100-41-4)

Xylene (CAS 1330-20-7)

**US. California Proposition 65**

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT):**

N-Methyl-2-pyrrolidinone (CAS 872-50-4)

Ethylbenzene(CAS 100-41-4)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non- Domestic Substances List (NDSL)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No


\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

**Issue date** 07-20-2000  
**Revision date** 08-26-2015  
**Version #** 01

**NFPA rating**



**References**

ACGIH: Documentation of the Threshold Limit Values and Biological Exposure indices  
 ECHA: European Chemicals Agency  
 HSDB: Hazardous Substances Data Bank  
 IARC: International Agency for Research on Cancer  
 NIOSH: The National Institute for Occupational Safety and



# SAFETY DATA SHEET

## PROFIN<sup>®</sup>SATIN

Revised Date: 08-26-2015

Supersedes: 07-20-2000

Health

NTP: National Toxicology Program

NLM: Hazardous Substances Data Base

OECD : Organization for Economic Co-operation and  
Development

OSHA: Occupational Safety and Health Administration

### Disclaimer

The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.