

Modular



iviay	20	IJ

Model Number	Daily Production Hourly Production		kW	Suggested Retail				
Frame / Modular	Gallons	Liters	Gallons	Liters	KVV	w/o APC		w/ APC
ATM14263+ / ATM14263+ APC	1400	5298	58	221	4.58	\$ 23,792.00	\$	26,411.00
ATM20263+ / ATM20263+ APC	2000	7568	83	315	4.58	\$ 25,339.00	\$	27,958.00
ATM25263+ / ATM25263+ APC	2500	9460	104	394	4.58	\$ 27,111.00	\$	29,729.00
ATM28263+ / ATM28263+ APC	2800	10595	117	441	4.58	\$ 27,500.00	\$	30,118.00
ATM36263+ / ATM36263+ APC	3600	13622	150	568	4.58	\$ 31,748.00	\$	34,366.00

Specify voltage when ordering: 208-220/3/60, 380-415/3/50, 440-460/3/60

Digital Remote Station: 4.3" Color HMI touch screen operator terminal, CD, UL and DNV Certified. Provides full watermaker control and system performance from a remote station. Complete with instructions and 75 feet of cable. NMEA 2000 Communication Module: Allows integration with NMEA 2000 control systems 57-4959 \$ 375.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter for product water of the 40 sq. ft. pleated commercial cartridges, 2 fresh water flush cartridges, 2 replacement oils and spare filter housing O-rings. Remember, the first service is at 50 hours! Media Filters / Iron Removal Filters: Automated, Media Filter for removal of particulate or p3-4976 particulate or p3-4976 particulate or p3-4976 particulate or p3-4976 particulate or p3-4977 product p3-4977 product p3-4977 product p3-4975 product	Atlas Options / Accessories	Part #	Suggested Retail			
Certified. Provides full watermaker control and system performance from a remote station. Complete with instructions and 75 feet of cable. NMEA 2000 Communication Module: Allows integration with NMEA 2000 control systems 57-4959 \$ 375.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 pH Neutralizer Assembly: Single pH neutralizing filter Nousing O-rings. Remember, the first service is at 50 hours! Media Filters / Iron Removal Filters: Automated, Media Filter for removal of particulate or Iron from the feed water stream. When required, the Media filter will shutdown the watermaker, automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Tank Size Flow Rate Part # 10" x 18" 5.5 GPM 07-1825 \$ 328.0 PH Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require 10-1825 \$ 328.0 PA 19-1825 \$ 328.0 P	Type Certified to not interfere with other bridge electronics. Provides full w	atermaker cor	ntrol and	50-4909	\$	1,738.00
PH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the pH of the product water 93-4973 \$ 155.0 Filter Replacement Kit: A perfect kit to keep your watermaker running smoothly. Includes 5 each of the 40 sq. ft. pleated commercial cartridges, 1 fresh water flush cartridges, 2 replacement oils and spare filter housing O-rings. Remember, the first service is at 50 hours! Media Filters / Iron Removal Filters: Automated, Media Filter for removal of particulate or Iron from the feed water stream. When required, the Media filter will shutdown the watermaker, automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Tank Size Flow Rate Size Flow Rate 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Finicron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron Ph Neutralizer Cartridge 2 x 10 Low pressure pump volute gasket 100 y 20-4972	•			50-4950	\$	998.00
Filter Replacement Kit: A perfect kit to keep your watermaker running smoothly. Includes 5 each of the 40 sq. ft. pleated commercial cartridges, 1 fresh water flush cartridges, 2 replacement oils and spare filter housing O-rings. Remember, the first service is at 50 hours! Media Filters / Iron Removal Filters: Automated, Media Filter for removal of particulate or Iron from the feed water stream. When required, the Media filter will shutdown the watermaker, automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Finiters / Iron Removal Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Finiters / Iron Removal Filters: Removal of taste, odor 10" x 18" 5.5 GPM 07-1825 Finiters / Iron Removal Filters: Removal of taste, odor 10" x 18" 5.5 GPM 07-1825 Finiters / Iron Removal Filters: Removal of taste, odor 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 mic	NMEA 2000 Communication Module: Allows integration with NMEA	2000 control	systems	57-4959	\$	375.00
of the 40 sq. ft. pleated commercial cartridges, 1 fresh water flush cartridges, 2 replacement oils and spare filter housing O-rings. Remember, the first service is at 50 hours! Media Filters / Iron Removal Filters: Automated, Media Filter for removal of particulate or Iron from the feed water stream. When required, the Media filter will shutdown the watermaker, automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables 5 micron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron PH Neutralizer Cartridge 2 x 10 Low pressure pump volute gasket MQFRK \$ 355.0 MQFRK \$ 93-4976 particulate 93-4977 lron \$ 9,975.0 93-4974 Particulate \$ 93-4974 Particulate \$ 93-4975 lron \$ 1,875.0 93-4975 lron \$ 1,875.0 93-4976 particulate \$ 1,875.0 93-4976 particulate \$ 1,875.0 93-4977 lron \$ 28-4975 lron \$ 328.0 1,875.	pH Neutralizer Assembly: Single pH neutralizing filter. Neutralizes the	pH of the pro	duct water	93-4973	\$	155.00
Iron from the feed water stream. When required, the Media filter will shutdown the watermaker, automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Fine Rate 10" x 18" 5.5 GPM 07-1825 Part # Suggested Retain Sugge	of the 40 sq. ft. pleated commercial cartridges, 1 fresh water flush cartridg	es, 2 replacer		MQFRK	\$	355.00
automatically position the backwash valves and backwashes. Saves expense on Prefilter. Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables 5 micron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron Fresh water flush cartridge 2 x 10 Low pressure pump seal kit Low pressure pump volute gasket	Media Filters / Iron Removal Filters: Automated, Media Filter for	removal of pa	rticulate or	93-4976 particulate	\$	9,975.00
particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Find Rate Size Flow Rate 93-4979 Part # Suggested Retain Suggested Suggested Retain Suggested Suggested Retain Suggested Suggested Retain Suggested Ret	•		93-4977 Iron	\$	9,975.00	
assembly and differential gauges. Granular Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to insure fresh water is clear and fresh when you drink it. Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Find Rate Size Flow Rate Part # Suggested Retain Size Flow Rate 93-4979 Call for Pricing Call for Pricing Fresh water flush cartridge, carbon block, 10 micron PH Neutralizer Cartridge 2 x 10 Low pressure pump volute gasket Size Flow Rate Size Flow Rate Size Flow Rate 93-4979 Call for Pricing Call for Pricing 43-2235 \$ 68.7 5 26.6 43-2235 \$ 89.9 5 26.6	Media Filters / Iron Removal Filters: Manual Back washable Media Filters for removal of particulate or Iron from the feed water stream. Saves expense on Prefilter. Includes valve tree assembly and differential gauges.		93-4974 Particulate	\$	1,875.00	
Activated Carbon Post Filters: Removal of taste, odor and chlorine from your fresh water. Installed after the fresh water tank to Size Flow Rate part # 10" x 18" 5.5 GPM 07-1825 \$328.0 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables Part # Suggested Retain 5 micron pleated Prefilter, 40 sq. ft., polyblend construction 20-2261 \$68.7 Fresh water flush cartridge, carbon block, 10 micron 20-0025 \$17.5 pH Neutralizer Cartridge 2 x 10 20-4972 \$52.6 Low pressure pump seal kit 43-2235 \$89.9 Low pressure pump volute gasket 5.0			93-4975 Iron	\$	1,875.00	
insure fresh water is clear and fresh when you drink it. 10" x 18" 5.5 GPM 07-1825 Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables 5 micron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron pH Neutralizer Cartridge 2 x 10 Low pressure pump seal kit 43-2235 \$ 89.9 Low pressure pump volute gasket	Granular Activated Carbon Post Filters: Removal of taste, odor	Tank Size	Flow Rate			
Hydrocyclone Separator: Maintenance free particulate removal down to 5 micron, may require larger feed pump Consumables 5 micron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron pH Neutralizer Cartridge 2 x 10 Low pressure pump seal kit Low pressure pump volute gasket Call for Pricing 93-4979 Call for Pricing 93-4979 Call for Pricing 20-2261 \$ 68.7 20-4972 \$ 52.6 43-2421 \$ 5.0		Size	Flow Rate	Part #	\$ 3	220.00
Larger feed pumpConsumablesPart #Suggested Retain5 micron pleated Prefilter, 40 sq. ft., polyblend construction20-2261\$68.7Fresh water flush cartridge, carbon block, 10 micron20-0025\$17.5pH Neutralizer Cartridge 2 x 1020-4972\$52.6Low pressure pump seal kit43-2235\$89.9Low pressure pump volute gasket43-2421\$5.0	insure fresh water is clear and fresh when you drink it.	10" x 18"	5.5 GPM	07-1825		328.00
5 micron pleated Prefilter, 40 sq. ft., polyblend construction Fresh water flush cartridge, carbon block, 10 micron pH Neutralizer Cartridge 2 x 10 Low pressure pump seal kit Low pressure pump volute gasket 20-2261 \$ 68.7 20-0025 \$ 17.5 20-4972 \$ 52.6 43-2235 \$ 89.9 43-2421 \$ 5.0	Hydrocyclone Separator: Maintenance free particulate removal down larger feed pump	to 5 micron, r	nay require	93-4979	Call for	Pricing
Fresh water flush cartridge, carbon block, 10 micron pH Neutralizer Cartridge 2 x 10 Low pressure pump seal kit Low pressure pump volute gasket 20-0025 \$ 17.5 20-4972 \$ 52.6 43-2235 \$ 89.9	Consumables			Part #	Sugg	ested Retail
pH Neutralizer Cartridge 2 x 10 20-4972 \$ 52.6 Low pressure pump seal kit 43-2235 \$ 89.9 Low pressure pump volute gasket 43-2421 \$ 5.0	5 micron pleated Prefilter, 40 sq. ft., polyblend construction			20-2261	\$	68.75
Low pressure pump seal kit 43-2235 \$ 89.9 Low pressure pump volute gasket 43-2421 \$ 5.0	Fresh water flush cartridge, carbon block, 10 micron			20-0025	\$	17.50
Low pressure pump volute gasket 43-2421 \$ 5.0	pH Neutralizer Cartridge 2 x 10			20-4972	\$	52.65
	Low proceure nump good kit				φ	
Pump oil 48-0199 \$ 18.7	Low pressure pump searkit			43-2235	Ф	89.95
	Low pressure pump volute gasket					89.95 5.00

