

# Interior Floor 350

## Interior Self Levelling Floor System

Water based tie-coat



### PRODUCT DESCRIPTION

Interior Floor 350 is a water based acrylic tie-coat specially designed to increase adhesion of Interior Floor 360/370 over Interior Floor 340 and epoxy primers.

- 1-component
- Water based
- Contains an additive to significantly increase adhesion under Interior Floor 360/370
- Odour free
- Short overcoating times

### PRODUCT INFORMATION

Product Code	YIF350
Finish	Matt, contains a slip resistance additive
Colour	Blue
Specific Gravity	1.3
Typical Shelf Life	1 year (unopened)
VOC (as supplied)	<10g / litre
Unit Size	3.8 Lt

### DRYING/OVERCOATING INFORMATION

	Drying			
	10°C (50°F)	15°C (59°F)	23°C (73°F)	35°C (95°F)
Touch Dry	40mins	40mins	30mins	20mins
Through Dry	50mins	50mins	40mins	20mins

	Overcoating							
	10°C (50°F)		15°C (59°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
Interior Floor 360	4hrs	24hrs	3hrs	24hrs	2hrs	24hrs	1hrs	24hrs
Interior Floor 370	4hrs	24hrs	3hrs	24hrs	2hrs	24hrs	1hrs	24hrs

### APPLICATION AND USE

#### Preparation

All substrates must be clean and dry. Interior Floor 350 is not suitable for areas of continuous or intermittent water/moisture.

#### PRIMED SUBSTRATES

In good condition: Clean and degrease with a suitable cleaner, rinse with fresh water and allow to dry.

In Poor Condition: Remove by mechanical means (SSPC-SP3/PWB (Powered wire brush)) and re prime with Interior Primer 330 WB or Interior Primer 860.

#### INTERIOR FLOOR 340

Interior Floor 350 should be applied over Interior Floor 340 just prior to overcoating with Interior Floor 360/370. Damaged areas of Interior Floor 340 must be fully removed and repaired before application of Interior Primer 350.



# Interior Floor 350

## Interior Self Levelling Floor System

Water based tie-coat



<b>Method</b>	<b>MIXING</b> Stir before and during use to ensure there is no settlement of the adhesion additive. Apply undiluted.  <b>APPLICATION</b> Interior Floor 350 should be applied by roller to the substrate, to produce a uniform covering of Interior Floor 350. Interior Floor 350 should not be allowed to pool at high wet film thicknesses on the substrate. Interior Floor 350 can be applied by brush in hard to reach areas.
<b>Hints</b>	<b>Mixing:</b> Stir before use. <b>Thinning:</b> Do not thin. <b>Application:</b> Care should be taken to minimise repeated rolling over the same area as this can cause pick up of the adhesion additive. It is important to ensure a closed coat of Interior Floor 350 is applied to the substrate. <b>Temperature:</b> Air temp should NOT be less than +15°C (59°F). <b>Cleaner:</b> Tools should be washed immediately in water.
<b>Some Important Points</b>	Do not use below 15°C / 59°F. Do not thin.
<b>Number of Coats</b>	1
<b>Coverage (Theoretical)</b>	6-7.5 m <sup>2</sup> /lt
<b>Recommended WFT</b>	125 microns
<b>Application Methods</b>	Roller, brush

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION</b> Exposure to air and extremes of temperature should be avoided. Interior Floor 350 must be kept in a frost free location. For the full shelf life of Interior Floor 350 to be realised ensure that the container is stored between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION</b> Interior Floor 350 should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Reminders of Interior Floor 350 cannot be disposed of through the municipal waste route or dumped without permit. Disposal of reminders must be arranged for in consultation with the authorities.
<b>IMPORTANT NOTES</b>	<i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</i>