

Salt Off Concentrate – Application Directions

To remove salt deposits from exterior marine surfaces, trailers, dive gear, fishing rods & reels:

Fill dispenser cup from the Salt Off® applicator (94100) with Salt Off Concentrate. Attach one end of applicator to a garden hose and the other end to a trigger-type garden hose nozzle. Ensure black knob on the applicator is in the “On” position and the blue knob is in the “Mixture” position.

Thoroughly saturate all surfaces that need to be treated, allowing Salt Off to soak in for 5 to 10 minutes. Stubborn deposits may require light brushing.

Rinse with fresh water and allow treated surfaces to air dry. No need to wipe.

To treat items by soaking:

Add 2 to 4 fl oz of Salt Off Concentrate per 1 gallon of fresh water. Immerse item to be treated for several minutes, rinse with fresh water and allow to air dry.

To flush inboard and outboard engines:

Fill Dispenser Cup with Salt Off Concentrate. Attach one end of applicator to a garden hose and the other end to a flushing unit designed for your engine type. Ensure black knob on the applicator is in the “On” position and the blue knob is in the “Water Only” position.

Run the engine to reach normal operating temperature. Once operating temperature has been reached, turn off the engine and turn the blue knob to “mixture” and verify the solution is flowing. Restart the engine and allow the engine to run until dispenser cup is clear, and the product has been used up.

Salt Off’s coating will protect the engine against future rust and corrosion.

NOTE: Do not store Salt Off Concentrate in applicator reservoir when not in use.