

Phoenix Inverters

180VA – 1200VA 230V/50Hz and 110V/60Hz

www.victronenergy.com



Phoenix Inverter
12/180

SinusMax – Superior engineering

Developed for professional duty, the Phoenix range of inverters is suitable for the widest range of applications. The design criteria have been to produce a true sine wave inverter with optimized efficiency but without compromise in performance. Employing hybrid HF technology, the result is a top quality product with compact dimensions, light in weight and capable of supplying power, problem-free, to any load.

Extra start-up power

A unique feature of the SinusMax technology is very high start-up power. Conventional high frequency technology does not offer such extreme performance. Phoenix Inverters, however, are well suited to power up difficult loads such as computers and low power electric tools.

To transfer the load to another AC source: the automatic transfer switch

For our lower power models we recommend the use of our Filax Automatic Transfer Switch. The Filax features a very short switchover time (less than 20 milliseconds) so that computers and other electronic equipment will continue to operate without disruption.

LED diagnosis

Please see manual for a description.

Remote on/off switch

Connector for remote on/off switch available on all models.

DIP switch for 50/60Hz selection (48/350 model only)

Available with different output sockets

Please see pictures below.




Phoenix Inverter
12/800 with Schuko socket



Phoenix Inverter 12/350
with IEC-320 sockets



Phoenix Inverter 12/180
with Schuko socket



Phoenix Inverter 12/180
with Nema 5-15R sockets



Phoenix Inverter 12/800
with IEC-320 socket



Phoenix Inverter 12/800
with Schuko socket



Phoenix Inverter 12/800
with BS 1363 socket



Phoenix Inverter 12/800
with AN/NZS 3112 socket



Phoenix Inverter 12/800
with Nema 5-15R socket

Phoenix Inverter	12 Volt 24 Volt 48 Volt	12/180 24/180	12/350 24/350 48/350	12/800 24/800 48/800	12/1200 24/1200 48/1200
Cont. AC power at 25°C (VA) (3)		180	350	800	1200
Cont. power at 25°C / 40°C (W)		175 / 150	300 / 250	700 / 650	1000 / 900
Peak power (W)		350	700	1600	2400
Output AC voltage / frequency (4)	110 VAC or 230 VAC +/- 3% 50 Hz or 60 Hz +/- 0,1%				
Input voltage range (V DC)	10,5 - 15,5 / 21,0 - 31,0 / 42,0 - 62,0			9,2 - 17,3 / 18,4 - 34,0 / 36,8 - 68,0	
Low battery alarm (V DC)	11,0 / 22 / 44			10,9 / 21,8 / 43,6	
Low battery shut down (V DC)	10,5 / 21 / 42			9,2 / 18,4 / 36,8	
Low battery auto recovery (V DC)	12,5 / 25 / 50			12,5 / 25 / 50	
Max. efficiency (%)	87 / 88	89 / 89/ 90		91 / 93 / 94	92 / 94 / 94
Zero load power (W)	2,6 / 3,8	3,1 / 5,0 / 6,0		6 / 5 / 4	6 / 5 / 6
Zero load power in search mode	n. a.	n. a.		2	2
Protection (2)	a - e				
Operating temperature range	-40 to +50°C (fan assisted cooling)				
Humidity (non-condensing)	max 95%				
ENCLOSURE					
Material & Colour	aluminium (blue Ral 5012)				
Battery-connection	1)	1)		1)	1)
Standard AC outlets	230V: IEC-320 (IEC-320 plug included), CEE 7/4 (Schuko) 120V: Nema 5-15R				
Other outlets (at request)	BS 1363 (United Kingdom) AN/NZS 3112 (Australia, New Zealand)				
Protection category	IP 20				
Weight (kg / lbs)	2,7 / 5,4	3,5 / 7,7		6,5 / 14.3	8,5 / 18.7
Dimensions (h x w x d in mm) (h x w x d in inches)	72x132x200 2.8x5.2x7.9	72x155x237 2.8x6.1x9.3		104 x 194 x 305 4.1 x 7.6 x 12.0	104 x 194 x 305 4.1 x 7.6 x 12.0
ACCESSORIES					
Remote on-off switch	Two pole connector				
Automatic transfer switch	Filax				
STANDARDS					
Safety	EN 60335-1				
Emission Immunity	EN 55014-1 / EN 55014-2/ EN 61000-6-2 / EN 61000-6-3				
1) Battery cables of 1.5 meter (12/180 with cigarette plug) 2) Protection key: a) output short circuit b) overload c) battery voltage too high d) battery voltage too low e) temperature too high	3) Non-linear load, crest factor 3:1 4) Frequency can be set by DIP switch (48/350 model only)				



Battery Alarm

An excessively high or low battery voltage is indicated by an audible and visual alarm, and a relay for remote signalling.



BMV-700 Battery Monitor

The BMV-700 Battery Monitor features an advanced microprocessor control system combined with high resolution measuring systems for battery voltage and charge/discharge current. Besides this, the software includes complex calculation algorithms to exactly determine the state of charge of the battery. The BMV-700 selectively displays battery voltage, current, consumed Ah or time to go. The monitor also stores a host of data regarding performance and use of the battery.