


Orion IP67 24/12 DC-DC Converter

Non isolated

www.victronenergy.com



Orion IP67 24/12-10
Orion IP67 24/12-20

Completely encapsulated: waterproof, shockproof and ignition protected

Water, oil or dirt will not damage the Orion IP67 DC-DC Converter. The casing is made of cast aluminium and the electronics are moulded in resin.

Extra-long input and output cables


Thanks to the cables of 1.8 meters in length, intermediate cable interconnections to increase length even more will in most cases not be needed. This is an important reliability increasing feature in an area where IP67 protection grade is needed.

Wide input voltage range

With 15 to 40 Volts input range, a stable output is ensured during surges or sags due to other equipment connected to same battery.

Protected against overheating

It can be used in a hot environment such as a machine room.



Orion IP67 24/12-5
with 1,8 m cables

Orion IP67	24/12-5		24/12-10	24/12-20
Input voltage range	15-40VDC			
Under voltage shutdown	13V			
Under voltage restart	14V			
No load current at 24V	1mA	20mA		50mA
DC output voltage	12V +/- 3%	12V +/- 3%		12V +/- 3%
Maximum continuous output current	5A	10A		20A
Efficiency	93%	93%		95%
Ripple & Noise	75mV pp			
Operating temperature range (derate 3% per °C above 40°C)	-20 to +70°C (full rated output up to 40°C)			
Overload protection	Hiccup mode, recovers automatically after fault condition is removed			
Short circuit proof	Yes			
Protection against reverse polarity connection	With external fuse or circuit breaker (not included)			
ENCLOSURE				
Material & Colour	Aluminium (blue RAL 5012)			
Protection category	IP67			
DC connection	Two input and two output cables, length 1,8m			
Cable cross section, input	0,8mm² (18 AWG)	1,5mm² (15 AWG)		2,6mm² (13 AWG)
Cable cross section, output	0,8mm² (18 AWG)	1,5mm² (15 AWG)		2,6mm² (13 AWG)
Weight (kg)	50 g	300 g		300 g
Dimensions (h x w x d in mm)	25 x 43 x 20	74 x 74 x 32		74 x 74 x 32
STANDARDS				
Safety	EN 60950			
Emission	EN 61000-6-3, EN 55014-1			
Immunity	EN 55014-2, EN 61000-6-1, EN 61000-6-2			
Automotive Directive	ECE R10-4			
Vibration	IEC 68-2-6: 10-150 Hz / 1.0 G			