

LITHIUM ION BATTERY DATASHEET

AVAILABLE IN:

240 Ah
12V



MORE POWER IN LESS SPACE

The Xantrex Lithium Ion Iron Phosphate (LiFePO₄) battery uses safety certified cells. Equipped with redundant safety features, the Xantrex lithium battery is the safest in the market today. Specifically designed to withstand the harsh operating environments of mobile applications, the Xantrex lithium battery lasts up to 6,000 cycles¹ compared to a traditional lead acid or AGM battery, which typically lasts 400-500 cycles. The Xantrex lithium battery offers exceptional power density and is also available with a heating blanket option if installation is outside the main cabin. With the Bluetooth connection enabled gathering real time data from the battery is incredibly simple and always accurate.



Internal BMS - reduces footprint



Cell Balancing - extends lifetime of battery



LED's to Monitor State of Charge



Remote Panel - view status of battery, turn battery on and off



Bluetooth - connect to the Xantrex mobile app to view status of battery



Parallel Stack up to 2 batteries

APPLICATIONS:




**10 YEAR
WARRANTY²**

www.xantrex.com
CUSTOMER CARE: 1.800.670.0707

Copyright © 2021 Xantrex LLC. All Rights Reserved. All trademarks are owned by Xantrex LLC.
V2. 08.30.2021

1: Up to 6,000 Cycles under ideal conditions

2: For full warranty details, please refer to our warranty policy document



COMING SOON


XANTREX APP

- Connect with bluetooth
- Monitor battery


DOWNLOAD ON




CONNECT WITH Bluetooth



240AH 12V DIMENSIONS



PARALLEL STACK UP TO 2 BATTERIES



BATTERY SPECIFICATION

Part Number	883-0240-12
Battery Voltage	12V
Nominal True Capacity	240Ah
Nominal Voltage	12.8 Volts
Nominal Watt Hours	3072Wh
Internal Impedence	<4mΩ
Charge Voltage	14.6V
Recommended Float Charge Voltage	13.6V
Recommended Charge Current	≤100A
Allowed Max Charge Current	150A
Output Voltage Range	10.0 - 14.6V
Recommended Discharge Current	100A
Max Continuous Discharge Current	150A
Pulse Discharge Current	300A (3s)
Discharge Cut-off Voltage	10V
Cycle Life to 80% Health	2800 (1.0C, 25°C, 80% Depth of Discharge) - increased cycle life with ideal conditions

ENVIRONMENTAL

Charging Temperature Range	32 - 131°F (0 - 55°C)
Discharging Temperature Range	-4 - 131°F (-20 - 55°C)
Storage Period 1 Week	-4 - 113°F (-20 - 45°C)
Storage Period 1 Month	14 - 113°F (-10 - 45°C)
Storage Period 6 Months	50 - 77°F (10 - 25°C)

MECHANICAL

Dimensions	19.7" x 7.1" x 10.3" (500mm x 180mm x 260mm)
Weight	69.4lbs (31.5kg)
Battery Terminals	M8 x 1.25
Carrying Capability	Two metal handles
Mouting Orientation	Standing

CERTIFICATION

U.N. International Approval	UN/DOT 38.3 Lithium Ion
-----------------------------	-------------------------

CONTACT

CUSTOMER SERVICE

1.800.670.0707
 customerservice@xantrex.com
Hours of operation:
 6:30am - 4:30pm PST, Monday to Friday



facebook.com/Xantrex



@Xantrex



youtube.com/XantrexTechnology

LEARN MORE ON:

www.xantrex.com